

Auto Cross Technical Specifications

1. Stock fuel tanks must be removed, unless they are in front of the rear axle. An auxiliary gas tank must be securely fastened and located behind front seat. US Coast Guard approved tanks are allowed.
2. Radiators must remain in stock location.
3. Cars need to have roof numbers!!!!
4. All doors must be securely welded or chained shut.
5. Roll bars and bars across drivers door are allowed for safety.
6. All cars must have working brakes.
7. All cars must have a 12" hole cut in hood above the air cleaner.
8. Drivers door must have original interior or padding on the inside.
9. Front and rear bumpers must match make and model of vehicle. (No trailer hitches allowed)
10. Absolutely no altering, welding or reinforcements of springs, frame, or other suspension components. All components must be stock.
11. One shock per wheel in stock location. No springs jacks, blocked shocks, coil over shocks, or air shocks.
12. Welding or chaining any parts to frame is prohibited. One 18" x 18" x 1/8" plate may be bolted to the frame to protect engine.
13. A minimum 2 ½ # ABC fire extinguisher securely fastened within reach of driver.
14. Throttle must have positive return springs.
15. Clear visible numbers must be on the top of the car.
16. No 4 wheel drives allowed. (cars only)

**All cars must pass tech inspection which runs from 4-6 p.m.
Race starts at 7:00 p.m.**